

**JP10279750A 19981020 RUBBER COMPOSITION CONSISTING ESSENTIALLY OF EPDM POLYMER AND RUBBER ROLLER FOR PAPER FEED USING THE SAME**

**Assignee/Applicant:** SUMITOMO RUBBER IND **Inventor(s)** : KAMISAKA KENICHI

**Priority (No,Kind,Date)** : JP8707197 A 19970404 X **Application(No,Kind,Date)**:

JP8707197 A 19970404 **IPC**: 6C 08L 23/16 A **Language of Document**: NotAvailable

**Abstract:**

**PROBLEM TO BE SOLVED:** To obtain a rubber composition consisting essentially of an ethylene- propylene-diene copolymer(EPDM polymer) and hardly depositing additives including a softener onto the surface.

**SOLUTION:** This rubber composition is produced by compounding 100 pts.wt. EPDM polymer with 30 pts.wt. hydrocarbon-based synthetic oil comprising an amorphous oligomer of ethylene with  $\alpha$ -olefin, 10 pts.wt. silica as a filler, 1 pt.wt. stearic acid as a filler, 5 pts.wt. zinc oxide as a filler, 2 pts.wt. sulfur and 1.3 pt.wt. curing accelerator and kneading these components at 120°C by using L- kneader.

**Legal Status:** There is no Legal Status information available for this patent